



visiServer Compact - 19 inches, 1 U

visiServer Compact - 19" 1 U - is a silent, high quality and high-availability compact server with visiomatic® touch screen connectivity. With its extremely low height of 67 mm the visiServer is especially attractive for rugged, densely packed server applications with long term availability.

Processor	Intel Celeron M series processor Intel® Core™2 Duo mobile processor
Housing	Massive Aluminium housing with passive cooling profile, black
Size (W x D x H)	Extreme Compact, 482 x 256 x 67 mm
Cooling	Temperature controlled silent fan, max. 2000rpm
Power	Low power consumption, optimized Power Supply, 250W, active PFC
Memory	2048 MB DDRAM, Kingston, Clock Rate PC533, CL5
Hard disk	80 GB, 8MB Cache, 5400rpm, 1.9W Power consumption

DVD drive

Slot-In DVD Drive, SlimLine

Connectors

2*GLAN network, VGA, DVI-D, 2 x RS232, 4 x USB
Stereo-Sound, Microphone

Extensions

1 x PCI slot, full size

Graphics

Mobile Intel® Graphics Media Accelerator X3100; Dynamic Video
Memory Technology 4.0

Audio

Realtek ALC262 2-channel High Definition Audio
Two 24-bit stereo DACs and three 20-bit stereo ADCs; S/PDIF
input/output interface

LAN

Two Realtek RTL8111B PCI Express Gigabit controllers
Supports 10Mbps, 100Mbps and 1Gbps data transmission

Ports

1 mini-DIN-6 PS/2 mouse port; 1 mini-DIN-6 PS/2 keyboard port
2 DB-9 serial ports (RS232/Power)
1 DB-15 VGA port; 1 DVI-I port (DVI-D signal only); 2 RJ45 LAN
ports; 4 USB 2.0/1.1 ports
Mic-in, line-in and line out jacks