

visiServer 19 compact 1.5 U



visiServer 19 inch 1,5 U compact is a silent, high quality and high-availability compact server with visiomatic touch screen connectivity. With its extremely low height of 67 mm the visiServer 19 compact is especially attractive for rugged, densely packed server applications with long term availability.

visiServer 19" compact 1.5 U

Technical Specification

| | |
|---------------------|--|
| Processor | Intel mobile Celeron M550 , 2GHz, 1MB Cache, FSB 533MHz |
| Housing | Massive Aluminium housing with passive cooling profile, black |
| Size | Extreme Compact, 482 x 256 x 67 (WDH in mm) |
| Cooling | Temperature controlled silent fan, max. 2000rpm |
| Power | Low power consumption, optimized Power Supply, 250W, active PFC |
| Memory | 2048 MB DDRAM, Kingston, Clock Rate PC533, CL5 |
| Hard disk | 80 GB, 8MB Cache, 5400rpm, 1.9W Power consumption |
| DVD drive | Slot-In DVD Drive, SlimLine |
| Connectors | 2*GLAN network, VGA, DVI-D, 2 x RS232, 4 x USB, Stereo-Sound, Microphone |
| Extensions | 1 x PCI slot, full size |
| Main board features | Internal graphics feature, Mobile Intel® Graphics Media Accelerator X3100, Dynamic Video Memory Technology 4.0, Microsoft supports up to QXGA (2048 x1536@60Hz) DVI 1.0 support for digital monitor Realtek ALC262 2-channel High Definition Audio, S/PDIF input/output Two Realtek RTL8111 PCI Express Gigabit controllers, Supports 10Mbps, 100Mbps and 1Gbps data transmission |